

WHAT IS CLAIMED IS:

1. A packet switch comprising:

a packet divider for dividing variable-length packets from a plurality of input lines into
5 fixed-length packets;

a plurality of input buffer sections provided corresponding to the plurality of input lines, each input buffer section having queues provided for each of mutually different priorities of a smaller number than
10 that of QoS classes that can be designated, and for each of a plurality of output lines, for registering fixed-length packets from corresponding input lines to corresponding queues according to the output line and the QoS class;

15 a scheduler for reading the fixed-length packets registered in the queues of the input buffer sections according to the priority given to each queue so that two or more fixed-length packets of the same output line are not read out within a unit time;

20 a switch for routing each fixed-length packet read out by the scheduler to a designated one output line out of the plurality of output lines; and

a plurality of output buffer sections provided corresponding to the plurality of output lines,
25 for carrying out an assembling of a variable-length packet from the fixed-length packets output from the switch and for controlling the priority based on the QoS class.

2. The packet switch of Claim 1, wherein

30 each input buffer section has a queue of a first priority and a queue of a second priority for each output line,

a packet of a bandwidth guaranteed class is registered in the queue of the first priority,

35 a packet of a best effort class is registered in the queue of the second priority,

a packet of a minimum bandwidth guaranteed

the queue of the second priority has a first drop level for dropping a packet of the minimum bandwidth guaranteed class that has been input in excess of a designated bandwidth and a packet of the best effort class, and a second drop level higher than the first drop level for dropping a packet of the minimum bandwidth guaranteed class that has been input within a designated bandwidth.

each output buffer section includes:
a variable-length packet assembling buffer
having queues of a number equal to the number of queues
for each output line in each input buffer section, for
15 each input line, for storing fixed-length packets output
from the switch into corresponding queues according to
the input line, thereby to assemble variable-length
packets from the fixed-length packets; and

4. The packet switch of Claim 1, wherein
each output buffer section includes:
a fixed-length-based QoS control section
having queues of a number equal to the number of QoS
classes that can be designated, for registering fixed-
length packets output from the switch into correspondin
queues according to the QoS class; and

a variable-length packet assembling buffer
having queues of a number equal to the number of QoS

classes that can be designated for each input line, for
registering the fixed-length packets output from the
fixed-length-based QoS control section into corresponding
queues according to the input line and the QoS class
5 thereby to assemble variable-length packets, and for
transferring the assembled variable-length packets to a
corresponding output line.

5. The packet switch of Claim 1, wherein
the scheduler selects fixed-length
10 packets, one by one, that are to be output to each output
line, by checking all the queues within the plurality of
input buffer sections in the order of priorities given to
the queues, in a predetermined order of input lines and
in a predetermined order of output lines, respectively,
15 within a unit time, and

in selecting an output line for
transmitting a fixed-length packet from the queue of the
same priority and the same input line, the scheduler
selects with priority over other fixed-length packets,
20 the fixed-length packet within the queue that corresponds
to the output line from which a part of a plurality of
fixed-length packets that constitute a variable-length
packet has already been transmitted.

6. The packet switch of Claim 3, wherein
25 the QoS control section includes:
means for adding a first value to a
corresponding token when a variable-length packet has
reached the front of one of the queues;
means for subtracting a second value from
30 each of tokens of active QoS classes each time when a
unit time has passed; and
means for starting the reading of a
variable-length packet of which corresponding token is a
minimum or 0 among the active QoS classes when a packet
35 can be sent to the output line.

7. The packet switch of Claim 6, wherein the first
value is a value corresponding to a packet length of the

variable-length packet that has reached the front of the queue, and the second value is a value corresponding to a ratio of a weight of each active QoS class to a total sum of the weights of the active QoS classes.

5 8. The packet switch of Claim 6, wherein the first value is a value corresponding to a product of a packet length of the variable-length packet that has reached the front of the queue and a total sum of the weights of the active QoS classes, and the second value is a value
10 corresponding to a weight of each active QoS class.

 9. The packet switch of Claim 8, wherein the first-value adding means adds the total sum of the weights of the active QoS classes to the token each time when a unit time has passed, and repeats this addition by
15 the number corresponding to the packet length, thereby adding the first value.

 10. The packet switch of Claim 3, wherein
 the QoS control section includes:
 a counter for counting for each QoS class
20 a number of fixed-length packets composing variable-length packets;
 a priority control section for determining and posting a QoS class of a packet to be output with priority based on a constant packet length, from out of
25 QoS classes that have count values other than 0; and
 a variable-length packet managing section for counting the posts from the priority control section for each QoS class, reading out a variable-length packet of the QoS class of which count value has reached a value
30 corresponding to the packet length of the variable-length packet at the front of a corresponding queue, and sending the read variable-length packet to the output line.

 11. The packet switch of Claim 3, wherein
 the QoS control section includes:
35 a first counter for counting for each QoS class a number of fixed-length packets composing variable-length packets of the bandwidth guaranteed class

and variable-length packets of the minimum bandwidth guaranteed class that have been input within a designated bandwidth;

5 a second counter for counting for each QoS class a number of fixed-length packets composing variable-length packets of the best effort class and variable-length packets of the minimum bandwidth guaranteed class that have been input in excess of the designated bandwidth;

10 a priority control section for determining and posting a QoS class of a packet to be output with priority based on a constant packet length, from out of QoS classes that have count values other than 0 for the first counter and QoS classes that have count values
15 other than 0 for the second counter; and

 a variable-length packet managing section for counting the posts from the priority control section for each QoS class, reading out a variable-length packet of the QoS class of which the count value has reached a
20 value corresponding to the packet length of the variable-length packet at the front of a corresponding queue, and sending the read variable-length packet to the output line.

12. The packet switch of Claim 6, wherein
25 the second value includes a second value for bandwidth guaranteed fraction and a second value for best effort fraction, and

 the second-value subtracting means subtracts only the second value for the bandwidth
30 guaranteed fraction from the token when there has been a packet reading from a bandwidth guaranteed class, and subtracts the second value for the bandwidth guaranteed fraction and the second value for the best effort fraction from the token when there has been no reading
35 from the bandwidth guaranteed class.

13. The packet switch of Claim 6, wherein
 the token includes a token for bandwidth

1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2808 2

10

15

14. A scheduling device comprising:

20

means for adding a first value to a corresponding token when a variable-length packet has reached a front of one of the queues;

25

30

35

16. The scheduling device of Claim 14, wherein the first value is a value corresponding to a product of a packet length of the variable-length packet that has reached the front of the queue and a total sum of the weights of the active QoS classes, and the second value is a value corresponding to a weight of each active QoS class.

17. The scheduling device of Claim 16, wherein the first-value adding means adds the total sum of the weights of the active QoS classes to the token each time when a unit time has passed, and repeats this addition by the number corresponding to the packet length, thereby adding the first value.

18. A scheduling device comprising:
queues provided in a number equal to a number of QoS classes that can be designated, for registering variable-length packets according to a QoS class;

a counter for counting for each QoS class a number of fixed-length packets composing variable-length packets;

a priority control section for determining and posting a QoS class of a packet to be output with priority based on a constant packet length, from out of QoS classes that have count values other than 0; and

a variable-length packet managing section for counting the posts from the priority control section for each QoS class, reading out a variable-length packet of the QoS class of which count value has reached a value corresponding to the packet length of the variable-length packet at the front of a corresponding queue, and sending the read variable-length packet to the output line.

19. A scheduling device comprising:
queues provided in a number equal to a number of QoS classes that can be designated, for registering variable-length packets according to a QoS class;

400200 SEE 1850

a first counter for counting for each QoS class a number of fixed-length packets composing variable-length packets of the bandwidth guaranteed class and variable-length packets of the minimum bandwidth guaranteed class that have been input within a designated bandwidth;

a second counter for counting for each QoS class a number of fixed-length packets composing variable-length packets of the best effort class and variable-length packets of the minimum bandwidth guaranteed class that have been input in excess of the designated bandwidth;

a priority control section for determining and posting a QoS class of a packet to be output with priority based on a constant packet length, from out of QoS classes that have count values other than 0 for the first counter and QoS classes that have count values other than 0 for the second counter; and

a variable-length packet managing section for counting the posts from the priority control section for each QoS class, reading out a variable-length packet of the QoS class of which count value has reached a value corresponding to the packet length of the variable-length packet at a front of a corresponding queue, and sending the read variable-length packet to the output line.

20. The scheduling device of Claim 14, wherein the second value includes a second value for bandwidth guaranteed fraction and a second value for best effort fraction, and

the second-value subtracting means subtracts only the second value for the bandwidth guaranteed fraction from the token when there has been a packet reading from the bandwidth guaranteed class, and subtracts the second value for the bandwidth guaranteed fraction and the second value for the best effort fraction from the token when there has been no reading from the bandwidth guaranteed class.

21. The scheduling device of Claim 14, wherein
the token includes a token for bandwidth
guaranteed fraction and a token for best effort fraction,
and the second value includes a second value for
5 bandwidth guaranteed fraction and a second value for best
effort fraction,

the second-value subtracting means
subtracts the second value for the bandwidth guaranteed
fraction and the second value for the best effort
10 fraction from the token for the bandwidth guaranteed
fraction and the token for the best effort fraction
respectively, and

when a packet to be read out has been
selected based on one of the token for the bandwidth
15 guaranteed fraction and the token for the best effort
fraction, the value subtracted from the other token for
the selected packet is carried forward to the token of a
next packet.

22. A drop control circuit comprising:
20 a calculation circuit for multiplying a
difference between a volume of packets stored in a buffer
and a threshold value thereof to a packet length of a
variable-length packet existing at a front of the buffer,
and outputting a result of the multiplication;
25 a register;
an adder circuit for adding a calculation
result of the calculation circuit to the register; and
a control circuit for dropping at once a
variable-length packet that exists at the front of the
30 buffer when a register value has exceeded a predetermined
value, and subtracting from the register a value obtained
by multiplying the packet length by the predetermined
value.

23. A drop control circuit comprising:
35 a calculation circuit for outputting a
difference between a volume of packets stored in a buffer
and a threshold value thereof;

a register;

an adder circuit for adding a calculation result of the calculation circuit to the register; and

5 a control circuit for dropping a fixed-length packet that exists at a front of the buffer when a register value has exceeded a predetermined value, and subtracting the predetermined value from the register.

24. A multicast control circuit comprising:

10 a multicast queue for registering an address of a variable-length packet to be multicast-controlled that is stored in a buffer;

a plurality of output buffer queues provided corresponding to a plurality of output lines;

15 an address management table for managing the address of a variable-length packet stored in the buffer; and

control means for storing as many records as there are output destinations into the address management table, each record including the address of the variable-length packet, and for registering addresses of the records in the output buffer queues corresponding to the output destinations, when the address of the variable-length packet to be multicast-controlled has been registered in the multicast queue.

25 25. A packet switch for switching a variable-length packet having a QoS class, the packet switch comprising:

means for mapping a plurality of QoS classes into simple priority classes; and

30 means for controlling the reading of the variable-length packets based on the simple priority classes.

26. A packet switch for converting an IP packet that has a QoS class into fixed-length packets, for switching the IP packet on the basis of the fixed-length packets, the packet switch comprising:

35 means for mapping priority classes of IP packets into simple priority classes of a smaller number

2025 RELEASE UNDER E.O. 14176

than the number of QoS classes that are allocated to the IP packets; and

means for controlling the reading of the fixed-length packets based on the simple priority classes.

27. A packet switch for converting an IP packet that has a QoS class into fixed-length packets, for switching the IP packet on the basis of the fixed-length packets, the packet switch comprising:

means for mapping priority classes of IP packets into simple priority classes of a smaller number than the number of QoS classes that are allocated to the IP packets;

means for controlling the reading of the fixed-length packets to the switch based on the simple priority classes; and

means for controlling the reading of the fixed-length packets after the switching based on the QoS classes allocated to the IP packets.

28. A QoS control device comprising:

a first selector for selecting one QoS class for reading a packet from at least one QoS class that belongs to a high-priority group;

a second selector for selecting one QoS class for reading a packet from at least one QoS class that belongs to a low-priority group; and

a third selector for selecting one of the high-priority group and the low-priority group, thereby selecting a packet of a QoS class selected by the first or second selector.

29. The QoS control device of Claim 28, wherein

a packet of a bandwidth guaranteed class and a packet of a minimum bandwidth guaranteed class that has been input within a designated bandwidth belong to the high-priority group, and a packet of a best effort class and a packet of the minimum bandwidth guaranteed class that has been input in excess of the designated

FOUO "SECRET"

bandwidth belong to the low-priority group, and

the packet of the minimum bandwidth guaranteed class is selected in the order of arrival irrespective of whether the packet has been selected as a packet within the designated bandwidth by the first selector or whether the packet has been selected as a packet outside the designated bandwidth by the second selector.

30. The QoS control device of Claim 28, wherein each of the first and second selectors selects one QoS class by round robin.

31. The QoS control device of Claim 28, wherein each of the first and second selectors selects a QoS class of a packet that has arrived the earliest.

32. The QoS control device of Claim 28, wherein each of the first and second selectors selects one QoS class out of packets that have arrived during an oldest period and that have not yet been selected.

33. The QoS control device of Claim 28, wherein each of the first and second selectors selects one QoS class according to a volume of packets that have not yet been selected.

34. A packet switch having a plurality of input lines for receiving packets and a plurality of output lines for sending packets, comprising:

a plurality of input buffer sections provided corresponding to the plurality of input lines, each input buffer section having queues provided for each of a plurality of output lines and for each of designated QoS classes, and for registering packets from corresponding input lines to corresponding queues according to the output line and a QoS class;

a scheduler for controlling the reading the packets registered in the queues of the input buffer sections so that two or more packets of the same output line are not read out within a unit time;

a switch for routing each packet read out

100-22-32-1-350

to a designated one output line out of the plurality of output lines; and

a plurality of output buffer sections provided corresponding to the plurality of output lines, for controlling the sending of the switched packet to the designated one output line according to a priority based on the QoS class.

35. The packet switch of Claim 34, wherein each input buffer section has a queue of a first priority and a queue of a second priority for each output line, and

each of said designated QoS classes is mapped into one of said first priority queue and said second priority queue.

36. The packet switch of Claim 35, wherein a packet of a bandwidth guaranteed class is registered in the first priority queue, a packet of a best effort class is registered in the second priority queue, a packet of a minimum bandwidth guaranteed class is registered in the second priority queue, and the second priority queue has a first drop level for dropping a packet of the minimum bandwidth guaranteed class that has been input in excess of a designated bandwidth and a packet of the best effort class, and a second drop level higher than the first drop level for dropping a packet of the minimum bandwidth guaranteed class that has been input within a designated bandwidth.

37. The packet switch of Claim 34, wherein each output buffer section includes: a QoS control section having queues of a number equal to a number of QoS classes that can be designated, for registering the packets into corresponding queues according to a QoS class, and for sequentially reading the packets according to a packet length and a QoS class and outputting the read packets to

2025 RELEASE UNDER E.O. 14176

corresponding output lines.

38. The packet switch of Claim 37, wherein
the QoS control section includes:

5 means for adding a first value to a
corresponding token when a packet has reached a front of
one of the queues;

means for subtracting a second value from
each of tokens of active QoS classes each time when a
unit time has passed; and

10 means for starting the reading of a packet
of which corresponding token is a minimum or 0 among the
active QoS classes when a packet can be sent to the
output line.

39. The packet switch of Claim 38, wherein the
15 first value is a value corresponding to a packet length
of the packet that has reached the front of the queue,
and the second value is a value corresponding to a ratio
of a weight of each active QoS class to a total sum of
the weights of the active QoS classes.

20 40. The packet switch of Claim 38, wherein the
first value is a value corresponding to a product of a
packet length of the packet that has reached the front of
the queue and a total sum of the weights of the active
QoS classes, and the second value is a value
25 corresponding to a weight of each active QoS class.

41. The packet switch of Claim 40, wherein the
first-value adding means adds the total sum of the
weights of the active QoS classes to the token each time
when a unit time has passed, and repeats this addition by
30 the number corresponding to the packet length, thereby
adding the first value.

42. A packet switch for switching packets each
packet having a QoS class, the packet switch comprising:
35 means for mapping a plurality of different
QoS classes into simple priority classes where a quantity
of simple priority classes is less than a quantity of the
plurality of different QoS classes; and

means for controlling the switching of the packets based on the simple priority classes.

43. A packet switch for converting an IP packet that has a QoS class into fixed-length packets, for switching the IP packet on the basis of the fixed-length packets, the packet switch comprising:

means for mapping priority classes of IP packets into simple priority classes of a smaller number than the number of QoS classes that are allocated to the IP packets;

means for controlling the switching of the fixed-length packets based on the simple priority classes; and

means for controlling the sending of the IP packets after switching based on the QoS classes allocated to the IP packets.

44. A method for switching packets in a packet switch having a plurality of input lines for receiving packets and a plurality of output lines for sending packets, comprising:

storing packets from the plurality of input lines to a plurality of input buffer sections provided corresponding to the plurality of input lines, each input buffer section having queues provided for each of a plurality of output lines and for each of designated QoS classes, and where packets from corresponding input lines are stored to corresponding queues according to the output line and a QoS class;

reading the packets stored in the queues of the input buffer sections so that two or more packets of the same output line are not read out within a unit time;

switching each packet read out to a designated one output line out of the plurality of output lines; and

sending the switched packet to the designated one output line according to a priority based

00013226 032004
00000000 00000000

5

10

15

20

25

30

35

subtracting a second value from each of
tokens of active QoS classes each time when a unit time

has passed; and

starting the reading of a packet of which corresponding token is a minimum or 0 among the active QoS classes when a packet can be sent to the output line.

5 49. The method of Claim 48, wherein the first value is a value corresponding to a packet length of a packet that has reached the front of the queue, and the second value is a value corresponding to a ratio of a weight of each active QoS class to a total sum of the weights of
10 the active QoS classes.

 50. The method of Claim 48, wherein the first value is a value corresponding to a product of a packet length of a packet that has reached the front of the queue and a total sum of weights of the active QoS classes, and the
15 second value is a value corresponding to a weight of each active QoS class.

 51. The method of Claim 50, wherein the first-value adding step adds the total sum of the weights of the active QoS classes to the token each time when a unit
20 time has passed, and repeats this addition by the number corresponding to the packet length, thereby adding the first value.

 52. A method of selecting a packet to be switched in a packet switch comprising the steps of:

25 mapping a plurality of different QoS classes designated for packets to be switched into a high-priority group and a low-priority group;

 selecting a QoS class of the high-priority group for reading a packet belonging to the selected QoS
30 class of the high-priority group;

 selecting a QoS class of the low-priority group for reading a packet belonging to the selected QoS class of the low-priority group; and

 selecting one of the high-priority group
35 and the low-priority group, thereby selecting for reading one of the selected packet belonging the high-priority group and the low-priority group.

2025 RELEASE UNDER E.O. 14176